



# Inductors

Military, MIL-PRF-15305 Qualified, Type LT  
and Commercial, Molded, Shielded, Miniature



### FEATURES

- Flame retardant coating.
- Electromagnetic shield.
- Small package for a shielded inductor.
- Epoxy molded construction provides superior moisture protection.
- Precision performance, excellent reliability, sturdy construction.

STANDARD ELECTRICAL SPECIFICATIONS										
IND. ( $\mu$ H)	TOL.	MILITARY STANDARD	MILITARY TYPE	Q MIN.	TEST FREQ. L & Q (MHz)	SELF- RESONANT FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED** DC CURRENT (mA)	INCREMENTAL*** CURRENT	
0.10	$\pm 10\%$	MS21426	LT10K	(Not QPL'd)	25.0	490.0	0.10	670	—	Iron Core
0.12	$\pm 10\%$	-1	518	54	25.0	430.0	0.11	635	—	
0.15	$\pm 10\%$	-2	519	52	25.0	415.0	0.12	610	—	
0.18	$\pm 10\%$	-3	520	50	25.0	375.0	0.13	585	—	
0.22	$\pm 10\%$	-4	521	49	25.0	330.0	0.15	545	—	
0.27	$\pm 10\%$	-5	522	47	25.0	300.0	0.16	530	—	
0.33	$\pm 10\%$	-6	523	46	25.0	260.0	0.18	495	—	
0.39	$\pm 10\%$	-7	524	44	25.0	230.0	0.19	485	—	
0.47	$\pm 10\%$	-8	525	42	25.0	220.0	0.21	460	—	
0.56	$\pm 10\%$	-9	526	41	25.0	210.0	0.23	440	—	
0.68	$\pm 10\%$	-10	527	41	25.0	180.0	0.24	430	—	
0.82	$\pm 10\%$	-11	528	39	25.0	165.0	0.27	405	—	
1.0	$\pm 10\%$	-12	529	38	25.0	150.0	0.30	385	—	
1.0	$\pm 10\%$	-13	530	37	25.0	150.0	0.30	385	—	
1.2	$\pm 10\%$	MS21426	LT10K		7.9	130.0	0.73	247	—	Iron Core
1.5	$\pm 10\%$	-14	531	40	7.9	115.0	0.86	228	—	
1.8	$\pm 10\%$	-15	532	41	7.9	105.0	0.95	217	—	
2.2	$\pm 10\%$	-16	533	43	7.9	95.0	1.1	202	—	
2.7	$\pm 10\%$	-17	534	45	7.9	90.0	1.2	193	—	
3.3	$\pm 10\%$	-18	535	48	7.9	80.0	1.3	185	—	
3.9	$\pm 10\%$	-19	536	49	7.9	75.0	1.5	173	—	
4.7	$\pm 10\%$	-20	537	50	7.9	70.0	2.4	136	—	
5.6	$\pm 10\%$	-21	538	53	7.9	60.0	2.9	124	—	
6.8	$\pm 10\%$	-22	539	54	7.9	55.0	3.2	118	—	
8.2	$\pm 10\%$	-23	540	55	7.9	53.0	3.6	111	—	
10.0	$\pm 10\%$	-24	541	55	7.9	50.0	4.0	106	—	
12.0	$\pm 10\%$	-25	542	57	7.9	35.0	3.0	122	—	
15.0	$\pm 10\%$	-26	543	36	2.5	30.0	3.4	115	—	
18.0	$\pm 10\%$	-27	544	38	2.5	26.0	3.8	108	—	
22.0	$\pm 10\%$	-28	545	40	2.5	24.0	4.9	96	—	
27.0	$\pm 10\%$	-29	546	40	2.5	21.0	5.8	88	—	
33.0	$\pm 10\%$	-30	547	40	2.5	20.0	6.5	83	—	
39.0	$\pm 10\%$	-31	548	41	2.5	19.0	7.9	75	—	
47.0	$\pm 10\%$	-32	549	42	2.5	16.0	9.3	69	—	
56.0	$\pm 10\%$	-33	550	44	2.5	15.0	11.0	64	—	
68.0	$\pm 10\%$	-34	551	44	2.5	13.0	12.0	61	—	
82.0	$\pm 10\%$	-35	552	45	2.5	11.0	13.0	59	—	
100.0	$\pm 10\%$	-36	553	45	2.5	10.5	16.8	51	—	
100.0	$\pm 10\%$	-37	554	40	2.5	10.5	16.8	51	—	
120.0	$\pm 10\%$	MS21427	LT10K	(Not QPL'd)	0.79	13.0	5.8	88	27	Ferrite Core
150.0	$\pm 10\%$	-1	555	31	0.79	12.0	7.9	75	24	
180.0	$\pm 10\%$	-2	556	33	0.79	11.0	9.4	69	22	
220.0	$\pm 10\%$	-3	557	33	0.79	10.0	11.0	64	20	
270.0	$\pm 10\%$	-4	558	35	0.79	9.0	12.0	61	18	
330.0	$\pm 10\%$	-5	559	37	0.79	8.0	16.0	53	16	
390.0	$\pm 10\%$	-6	560	40	0.79	7.8	21.0	46	14	
470.0	$\pm 10\%$	-7	561	38	0.79	7.5	24.0	43	13	
560.0	$\pm 10\%$	-8	562	36	0.79	7.0	28.0	40	12	
560.0	$\pm 10\%$	-9	563	36	0.79	7.0	28.0	40	12	

\*Measured with full length lead. \*\*Rated DC Current: Based on the maximum temperature rise not to exceed 15°C at + 90°C ambient.

\*\*\*Incremental Current: The minimum typical current at which the inductance will be decreased by 5% from its initial zero DC value.

### ELECTRICAL SPECIFICATIONS

**Inductance Tolerance:**  $\pm 10\%$  standard.  $\pm 5\%$  available.

**Insulation Resistance:** 1000 Megohm minimum per MIL-STD-202, Method 302, Test Condition B.

**Dielectric Withstanding Voltage:** 200 VAC per MIL-STD-202, Method 301 (sea level).

**Percent Coupling:** 3% maximum per MIL-PRF-15305.

**Operating Temperature Range:** - 55°C to + 105°C.



**MECHANICAL SPECIFICATIONS**

**Terminal Strength:** 3 pounds pull per MIL-STD-202, Method 211, Test Condition A except 180° rotation for a total of 540°C.

**Weight:** IMS-2 = 0.30 grams maximum.

**MATERIAL SPECIFICATIONS**


**Encapsulant:** Epoxy.

**Standard Terminal:** #24 AWG tinned copper.

**TEST EQUIPMENT\***

- H/P 4342A Q-Meter.
- Measurements Corporation Megacycle Meter, Model 59.
- Wheatstone Bridge.

\*Test procedures per MIL-PRF-15305.



INDUCTANCE RANGE AND MILITARY STANDARD						
INDUCTANCE RANGE		CLASSIFICATION		MATERIAL		MILITARY STANDARD
FROM	TO	GRADE	CLASS	CORE	SHIELD	
0.10µH	100µH	1	A	Powdered Iron	Powdered Iron	MS21426
120µH	560µH	1	A	Ferrite	Ferrite	MS21427

ENVIRONMENTAL PERFORMANCE		
TEST	CONDITIONS	SPECIFICATIONS
Barometric Pressure	Test Condition C	MIL-STD-202, Method 105
Thermal Shock	Test Condition A-1	MIL-STD-202, Method 107
Flammability	—	MIL-STD-202, Method 111
Overload	—	MIL-PRF-15305
Low Temperature Storage	—	MIL-PRF-15305
Resistance to Soldering Heat	Test Condition A	MIL-STD-202, Method 210
Resistance to Solvents	—	MIL-STD-202, Method 215

ORDERING INFORMATION		
IMS-2 MODEL	10µH INDUCTANCE VALUE	± 10% INDUCTANCE TOLERANCE

ORDERING INFORMATION - MILITARY PART NUMBER						
MS21426 MILITARY STANDARD	- 14 INDUCTANCE VALUE	OR	LT TYPE	10 GRADE AND CLASS	K FAMILY	531 ID NUMBER

**NOTE:** Listing of military standard does not imply qualification. Contact factory for latest government QPL information.



## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.