
KEMET Part Number: T110C476M020AS7200

(T110C476M020AS7443, T110C476M020ASTR)



Capacitor, Tantalum, 47 uF, +/-20% Tol, 20V@85C



Dimensions (mm)			
Symbol	Dimension	Tolerance	
D	7.34	+/-0.25	
L	17.42	+/-0.79	
L2	20.88		
F	0.64	+/-0.05	
LL	38.1	+/-6.35	

Notes:

-Dimensions include insulating sleve (standard)

-When supplied on T&R or AMMO, lead length is determined by taping specification.

General Information			
Supplier:	KEMET		

Specifications		
Value:	47 uF	
Voltage DC @ 85C:	20V	
Voltage DC @ 125C:	13V	
Tolerance:	+/-20%	
Application:	General Purpose	
Body Type:	Axial Hermetic ('cs13-style')	
Temperature Range:	-55/+125C	
Termination Type:	Tin-Lead (SnPb)	
ESR:	1.2 Ohm	
ESR Frequency @ 25C:	100 kHz	
Leakage Current:	4.5 uA	
Dissipation Factor:	6%	

Packaging Specifications		
Package Kind:	T&R	
Package Type:	Class III (b=73mm)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

