


PROGRAMMABLE HIGH-FREQUENCY CRYSTAL OSCILLATOR

SG-8002CA series

- Wide frequency output by PLL technology.
- Quick delivery of samples and short lead mass production time.
- Excellent shock resistance and environmental capability.
- Output enable function (OE) and stand-by function (ST) can be used for low current consumption applications.

8002 PROM Writer available to purchase.(Type:PRW-8000A3-M01)
Please contact EPSON or local sales representative.



Specifications (characteristics)


Item	Symbol	PT/ST	PH/SH	PC/SC	Remarks
		Specifications			
Output frequency range	f_o		1.0000 MHz to 125.0000 MHz		
Power source voltage	Max. supply voltage	V_{DD-GND}	-0.5V to +7.0V		
	Operating voltage	V_{DD}	5.0V±0.5V	3.3 ± 0.3V	3.0V ±0.3V: $f_o \leq 66.7$ MHz(PC/SC)
Temperature range	Storage temperature	T_{STG}	-55°C to +125°C		
	Operating temperature	T_{OPR}	-20°C to +70°C (-40°C to +85°C)	-40°C to +85°C	Refer to page 4."Frequency range"
Soldering condition	T_{SOL}	Twice at under 260°C within 10 sec. or under 230°C within 3 min.			
Frequency stability	$\Delta f/f_o$	B: ±50ppm C: ±100ppm M: ±100ppm(-40°C to +85°C)			-20°C to +70°C
Current consumption	I_{OP}	45mA max.		28mA max.	No load condition, Max. frequency range
Output disable current	I_{OE}	30mA max.		16mA max.	OE=GND
Standby current	I_{ST}	50µA max.			ST=GND
Duty	t_w/t	—	40% to 60%		C-MOS load: 1/2 V_{DD} level
		40% to 60%	—		TTL load: 1.4V level
High output voltage	V_{OH}	$V_{DD} - 0.4V$ min.			$I_{OH} = -16$ mA(PT/ST,PH/SH), -8mA(PC/SC)
Low output voltage	V_{OL}	0.4V max.			$I_{OL} = 16$ mA(PT/ST,PH/SH), 8mA(PC/SC)
Output load condition (fan out)	TTL	N	5TTL max.	—	Max. frequency and max. operating voltage range
	C-MOS	C_L	15pF max.	15pF max.	
Output enable/disable input voltage		V_{IH}	2.0V min.	$0.7 \times V_{DD}$ min.	\overline{ST} , OE terminal
		V_{IL}	0.8V max.	$0.2 \times V_{DD}$ max.	
Output rise time	C-MOS level	t_{TLH}	—	4ns max.	C-MOS load: 20%→80% V_{DD}
	TTL level		4ns max.	—	TTL load: 0.4V→2.4V
Output fall time	C-MOS level	t_{THL}	—	4ns max.	C-MOS load: 80%→20% V_{DD}
	TTL level		4ns max.	—	TTL load: 2.4V→0.4V
Oscillation start up time	t_{OSC}	10ms max.			Time at minimum operating voltage to be 0 sec.
Aging	f_a	±5ppm/year max.			$T_a = 25^\circ\text{C}$, $V_{DD} = 5.0V/3.3V$ (PC/SC)
Shock resistance	S.R.	±20ppm max.			Three drops on a hard board from 75 cm or excitation test with 3000G x 0.3ms x 1/2sine wave in 3 directions

Note: • Please contact us for inquiries about operating temperature(-40°C to +85°C), usable frequencies, duty and output load conditions. Checking possible by the Frequency Checking Program.

<http://www.epson.co.jp/CRYSTAL/>


External dimensions

(Unit: mm)



Recommended soldering pattern

(Unit: mm)



THE CRYSTALMASTER




ENERGY SAVING EPSON

EPSON offers effective savings to its customers through a wide range of electronic devices, such as semiconductors, liquid crystal display (LCD) modules, and crystal devices. These savings are achieved through a sophisticated melding of three different efficiency technologies.

Power saving technology provides low power consumption at low voltages.

Space saving technology provides further reductions in product size and weight through super-precise processing and high-density assembly technology.

Time saving technology shortens the time required for design and development on the customer side and shortens delivery times.



Our concept of Energy Saving technology conserves resources by blending the essence of these three efficiency technologies. The essence of these technologies is represented in each of the products that we provide to our customers.

In the industrial sector, leading priorities include measures to counter the greenhouse effect by reducing CO₂, measures to preserve the global environment, and the development of energy-efficient products. Environmental problems are of global concern, and although the contribution of energy-saving technology developed by EPSON may appear insignificant, we seek to contribute to the development of energy-saving products by our customers through the utilization of our electronic devices. EPSON is committed to the conservation of energy, both for the sake of people and of the planet on which we live.



SEIKO EPSON CORP. QUARTZ DEVICE DIVISION acquired ISO9001 and ISO14001 certification by B.V.Q.I. (Bureau Veritas Quality International) .

ISO9001 in October, 1992.

ISO14001 in November, 1997.

NOTICE

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. This material or portions there may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Control Law of Japan and may require an export license from the Ministry of International Trade and Industry or other approval from another government agency.