

PowerMOS transistor

GENERAL DESCRIPTION

N-channel enhancement mode field-effect power transistor in a plastic envelope.

The device is intended for use in Switched Mode Power Supplies (SMPS), motor control, welding, DC/DC and AC/DC converters, and in general purpose switching applications.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	BUK455	MAX. -50A	MAX. -50B	UNIT
V_{DS}	Drain-source voltage	50	50	50	V
I_D	Drain current (DC)	41	41	38	A
P_{tot}	Total power dissipation	125	125	125	W
T_J	Junction temperature	175	175	175	°C
$R_{DS(ON)}$	Drain-source on-state resistance	0.038	0.045	0.045	Ω

MECHANICAL DATA

Dimensions in mm

Net Mass: 2g

Pinning:

1 = Gate

2 = Drain

3 = Source





Fig.1 TO220AB; drain connected to mounting base.

blue binder, tab 4

Notes

- Observe the general handling precautions for electrostatic-discharge sensitive devices (ESDs) to prevent damage to MOS gate oxide.
- Accessories supplied on request: refer to Mounting instructions for TO220 envelopes.



RATINGS

Limiting values in accordance with the Absolute Maximum System (IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.		UNIT
V_{DS} V_{DSS} $\pm V_{GS}$	Drain-source voltage	-	-	50		V
	Drain-gate voltage	$R_{GS} = 20 \text{ k}\Omega$	-	50		V
	Gate-source voltage	-	-	30		V
I_D I_D I_{DM}	Drain current (DC)	$T_{mb} = 25^\circ\text{C}$	-	-50A	-50B	A
	Drain current (DC)	$T_{mb} = 100^\circ\text{C}$	-	41	38	A
	Drain current (pulse peak value)	$T_{mb} = 25^\circ\text{C}$	-	29	27	A
P_{tot} T_{stg} T_J	Total power dissipation	$T_{mb} = 25^\circ\text{C}$	-	164	152	A
	Storage temperature	-	-55	125		W
	Junction Temperature	-	-	175	175	°C

THERMAL RESISTANCES

From junction to mounting base	$R_{th,j-mb} = 1.2 \text{ K/W}$
From junction to ambient	$R_{th,j-a} = 60 \text{ K/W}$

STATIC CHARACTERISTICS $T_{mb} = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0 \text{ V}; I_D = 0.25 \text{ mA}$	50	-	-	V
$V_{GS(10)}$	Gate threshold voltage	$V_{DS} = V_{GS}; I_D = 1 \text{ mA}$	2.1	3.0	4.0	V
I_{DSS}	Zero gate voltage drain current	$V_{DS} = 50 \text{ V}; V_{GS} = 0 \text{ V}; T_J = 25^\circ\text{C}$	-	1	10	μA
I_{BS}	Zero gate voltage drain current	$V_{DS} = 50 \text{ V}; V_{GS} = 0 \text{ V}; T_J = 125^\circ\text{C}$	-	0.1	1.0	mA
I_{GS}	Gate source leakage current	$V_{GS} = \pm 30 \text{ V}; V_{DS} = 0 \text{ V}$	-	10	100	nA
$R_{DS(ON)}$	Drain-source on-state resistance	$V_{GS} = 10 \text{ V}; I_D = 20 \text{ A}$ BUK455-50A BUK455-50B	-	0.03	0.038	Ω

DYNAMIC CHARACTERISTICS $T_{mb} = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
g_{fs}	Forward transconductance	$V_{DS} = 25 \text{ V}; I_D = 20 \text{ A}$	8	13.5	-	S
C_{iss} C_{oss} C_{res}	Input capacitance Output capacitance Feedback capacitance	$V_{GS} = 0 \text{ V}; V_{DS} = 25 \text{ V}; f = 1 \text{ MHz}$	-	1650 560 300	2000 750 400	pF pF pF
$t_{d(on)}$ t_r $t_{d(off)}$ t_f	Turn-on delay time Turn-on rise time Turn-off delay time Turn-off fall time	$V_{DD} = 30 \text{ V}; I_D = 3 \text{ A};$ $V_{GS} = 10 \text{ V}; R_{GS} = 50 \Omega;$ $R_{gen} = 50 \Omega$	-	25 60 125 100	40 90 160 130	ns ns ns ns
L_d L_s L_i	Internal drain inductance Internal source inductance Internal drain inductance	Measured from contact screw on tab to centre of die Measured from drain lead 6 mm from package to centre of die Measured from source lead 6 mm from package to source bond pad	-	3.5 4.5 7.5	-	nH nH nH

REVERSE DIODE RATINGS AND CHARACTERISTICS

 $T_{mb} = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
I_{DR}	Continuous reverse drain current	-	-	-	41	A
I_{DRM}	Pulsed reverse drain current	-	-	-	164	A
V_{SD}	Diode forward voltage	$I_F = 41 \text{ A}; V_{GS} = 0 \text{ V}$	-	1.4	2.0	V
t_{RQ}	Reverse recovery time	$I_F = 41 \text{ A}; -dI_F/dt = 100 \text{ A}/\mu\text{s}$	-	250	-	ns
	Reverse recovery charge	$V_{GS} = 0 \text{ V}; V_R = 30 \text{ V}$	-	0.30	-	μC

AVALANCHE RATING

 $T_{mb} = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
W_{DSS}	Drain-source non-repetitive unclamped inductive turn-off energy	$I_D = 41 \text{ A}; V_{DD} \leq 25 \text{ V}; V_{GS} = 10 \text{ V}; R_{GS} = 50 \Omega$	-	-	100	mJ




Fig.2. Normalised power dissipation.
 $PD\% = 100 \cdot P_D / P_{D, 25^\circ\text{C}} = f(T_{mb})$




Fig.4. Safe operating area. $T_{mb} = 25^\circ\text{C}$
 I_D & $I_{DM} = f(V_{DS})$; I_{DM} single pulse; parameter t_p




Fig.3. Normalised continuous drain current.
 $ID\% = 100 \cdot I_D / I_{D, 25^\circ\text{C}} = f(T_{mb})$; conditions: $V_{GS} \geq 10 \text{ V}$




Fig.5. Transient thermal impedance.
 $Z_{th,j-mb} = f(t);$ parameter $D = t_p/T$




Fig.6.1 Typical output characteristics, $T_j = 25^\circ\text{C}$.
 $I_D = f(V_{DS})$; parameter V_{GS}




Fig.9. Typical transconductance, $T_j = 25^\circ\text{C}$.
 $g_{ds} = f(I_D)$; conditions: $V_{DS} = 25\text{ V}$




Fig.7. Typical on-state resistance, $T_j = 25^\circ\text{C}$.
 $R_{DS(ON)} = f(I_D)$; parameter V_{GS}




Fig.10. Normalised drain-source on-state resistance.
 $a = R_{DS(ON)}/R_{DS(ON)25^\circ\text{C}} = f(T_j)$; $I_D = 20\text{ A}$; $V_{GS} = 10\text{ V}$




Fig.8. Typical transfer characteristics.
 $I_D = f(V_{GS})$; conditions: $V_{DS} = 25\text{ V}$; parameter T_j




Fig.11. Gate threshold voltage.
 $V_{GS(TO)} = f(T_j)$; conditions: $I_D = 1\text{ mA}$; $V_{DS} = V_{GS}$




Fig.12. Sub-threshold drain current.
 $I_D = f(V_{GS})$; conditions: $T_J = 25^\circ\text{C}$; $V_{DS} = V_{GS}$




Fig.15. Typical reverse diode current.
 $I_F = f(V_{DS})$; conditions: $V_{GS} = 0\text{ V}$; parameter $T_J / ^\circ\text{C}$




Fig.13. Typical capacitances, C_{iss} , C_{oss} , C_{rss} .
 $C = f(V_{DS})$; conditions: $V_{GS} = 0\text{ V}$; $f = 1\text{ MHz}$




Fig.16. Normalised avalanche energy rating.
 $W_{DSS}\% = f(T_{mb})$; conditions: $I_D = 41\text{ A}$




Fig.14. Typical turn-on gate-charge characteristics.
 $V_{GS} = f(Q_G)$; conditions: $I_D = 41\text{ A}$; parameter V_{DS}




Fig.17. Avalanche energy test circuit.
 $W_{DSS} = 0.5 \cdot L I_D^2 \cdot BV_{DSS} / (BV_{DSS} - V_{DD})$