


SIPMOS® Power Transistor

- N-Channel
- Enhancement mode
- Avalanche rated
- Logic Level
- dv/dt rated
- 175°C operating temperature



Pin 1	Pin 2	Pin 3
G	D	S

Type	V _{DS}	I _D	R _{DS(on)}	@ V _{GS}	Package	Ordering Code
SPB70N10L	100 V	70 A	0.025 Ω	V _{GS} = 4.5 V	P-TO263-3-2	Q67040-S4170
SPP70N10L			0.016 Ω	V _{GS} = 10 V	P-TO220-3-1	Q67040-S4175

Maximum Ratings, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current $T_C = 25^\circ\text{C}$	I _D	70	A
$T_C = 100^\circ\text{C}$		50	
Pulsed drain current $T_C = 25^\circ\text{C}$	I _{Dpulse}	280	
Avalanche energy, single pulse $I_D = 70 \text{ A}, V_{DD} = 25 \text{ V}, R_{GS} = 25 \Omega$	E _{AS}	1000	mJ
Avalanche current, periodic limited by $T_{j(\max)}$	I _{AR}	70	A
Avalanche energy, periodic limited by $T_{j(\max)}$	E _{AR}	25	mJ
Reverse diode dv/dt $I_S = 70 \text{ A}, V_{DD} \leq V_{(BR)DSS}, dI/dt = 200 \text{ A}/\mu\text{s}, T_{j(\max)} = 175^\circ\text{C}$	dv/dt	6	kV/μs
Gate source voltage	V _{GS}	±14	V
Gate source peak voltage, $t_p \leq 100\mu\text{s}$	V _{gs}	±20	
Power dissipation $T_C = 25^\circ\text{C}$	P _{tot}	250	W
Operating temperature	T _j	-55 ... +175	°C
Storage temperature	T _{stg}	-55 ... +175	
IEC climatic category; DIN IEC 68-1		55/175/56	

Electrical Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
at $T_j = 25^\circ\text{C}$, unless otherwise specified					

Thermal Characteristics

Thermal resistance, junction - case	R_{thJC}	-	tbd	0.6	K/W
Thermal resistance, junction - ambient	R_{thJA}	-	62.5	-	
SMD version, device on PCB: @ min. footprint @ 6 cm ² cooling area ¹⁾	R_{thJA}	-	tbd	-	

Static Characteristics

Drain- source breakdown voltage $V_{GS} = 0 \text{ V}$, $I_D = 0.25 \text{ mA}$	$V_{(\text{BR})DSS}$	100	-	-	V
Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D = 240 \mu\text{A}$	$V_{GS(\text{th})}$	1.2	1.6	2	
Zero gate voltage drain current $V_{DS} = 100 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_j = 25^\circ\text{C}$ $V_{DS} = 100 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_j = 150^\circ\text{C}$	I_{DSS}	-	0.1	1	μA
Gate-source leakage current $V_{GS} = 20 \text{ V}$, $V_{DS} = 0 \text{ V}$	I_{GSS}	-	10	100	nA
Drain-Source on-state resistance $V_{GS} = 4.5 \text{ V}$, $I_D = 50 \text{ A}$ $V_{GS} = 10 \text{ V}$, $I_D = 50 \text{ A}$	$R_{DS(\text{on})}$	-	0.014	0.025	Ω
		-	0.01	0.016	

¹ Device on 50mm*50mm*1.5mm epoxy PCB FR4 with 6 cm² (one layer, 70μm thick) copper area for drain connection. PCB is vertical without blown air.

Electrical Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
at $T_j = 25^\circ\text{C}$, unless otherwise specified					

Dynamic Characteristics

Transconductance $V_{DS} \geq 2 * I_D * R_{DS(on)max}$, $I_D = 50\text{ A}$	g_{fs}	30	65	-	S
Input capacitance $V_{GS} = 0\text{ V}$, $V_{DS} = 25\text{ V}$, $f = 1\text{ MHz}$	C_{iss}	-	3630	4540	pF
Output capacitance $V_{GS} = 0\text{ V}$, $V_{DS} = 25\text{ V}$, $f = 1\text{ MHz}$	C_{oss}	-	640	800	
Reverse transfer capacitance $V_{GS} = 0\text{ V}$, $V_{DS} = 25\text{ V}$, $f = 1\text{ MHz}$	C_{rss}	-	345	430	
Turn-on delay time $V_{DD} = 30\text{ V}$, $V_{GS} = 4.5\text{ V}$, $I_D = 70\text{ A}$, $R_G = 1.3\Omega$	$t_{d(on)}$	-	70	105	ns
Rise time $V_{DD} = 30\text{ V}$, $V_{GS} = 4.5\text{ V}$, $I_D = 70\text{ A}$, $R_G = 1.3\Omega$	t_r	-	250	375	
Turn-off delay time $V_{DD} = 30\text{ V}$, $V_{GS} = 4.5\text{ V}$, $I_D = 70\text{ A}$, $R_G = 1.3\Omega$	$t_{d(off)}$	-	250	375	
Fall time $V_{DD} = 30\text{ V}$, $V_{GS} = 4.5\text{ V}$, $I_D = 70\text{ A}$, $R_G = 1.3\Omega$	t_f	-	95	145	

Electrical Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
at $T_j = 25^\circ\text{C}$, unless otherwise specified					

Dynamic Characteristics


Gate charge at threshold $V_{DD} = 80 \text{ V}, I_D \geq 0,1 \text{ A}, V_{GS} = 0 \text{ to } 1 \text{ V}$	$Q_{G(\text{th})}$	-	10	15	nC
Gate charge at $V_{GS}=5\text{V}$ $V_{DD} = 80 \text{ V}, I_D = 70 \text{ A}, V_{GS} = 0 \text{ to } 5 \text{ V}$	$Q_{g(5)}$	-	74	110	
Gate charge total $V_{DD} = 80 \text{ V}, I_D = 70 \text{ A}, V_{GS} = 0 \text{ to } 10 \text{ V}$	Q_g	-	160	240	nC
Gate plateau voltage $V_{DD} = 80 \text{ V}, I_D = 70 \text{ A}$	$V_{(\text{plateau})}$	-	3.22	-	V

Reverse Diode

Inverse diode continuous forward current $T_C = 25^\circ\text{C}$	I_S	-	-	70	A
Inverse diode direct current,pulsed $T_C = 25^\circ\text{C}$	I_{SM}	-	-	280	
Inverse diode forward voltage $V_{GS} = 0 \text{ V}, I_F = 140 \text{ A}$	V_{SD}	-	1.2	1.8	V
Reverse recovery time $V_R = 80 \text{ V}, I_F=I_S, di_F/dt = 100 \text{ A}/\mu\text{s}$	t_{rr}	-	100	150	ns
Reverse recovery charge $V_R = 80 \text{ V}, I_F=I_S, di_F/dt = 100 \text{ A}/\mu\text{s}$	Q_{rr}	-	600	900	nC

Power Dissipation


$$P_{\text{tot}} = f(T_C)$$



Drain current

$$I_D = f(T_C)$$

parameter: $V_{GS} \geq 10$ V



Transient thermal impedance


$$Z_{\text{thJC}} = f(t_p)$$

parameter: $D = t_p/T$

Typ. output characteristics

$$I_D = f(V_{DS})$$


parameter: $t_p = 80 \mu\text{s}$



Drain-source on-resistance

$$R_{DS(on)} = f(T_j)$$


parameter : $I_D = 50 \text{ A}$, $V_{GS} = 4.5 \text{ V}$



Typ. transfer characteristics $I_D = f(V_{GS})$

parameter: $t_p = 80 \mu\text{s}$


$$V_{DS} \geq 2 \times I_D \times R_{DS(\text{on})\text{max}}$$



Typ. capacitances

$$C = f(V_{DS})$$


Parameter: $V_{GS}=0 \text{ V}$, $f=1 \text{ MHz}$



Gate threshold voltage

$$V_{GS(\text{th})} = f(T_j)$$


parameter : $V_{GS} = V_{DS}$, $I_D = 240 \mu\text{A}$



Forward characteristics of reverse diode

$$I_F = f(V_{SD})$$


parameter: T_j , $t_p = 80 \mu\text{s}$



Avalanche Energy $E_{AS} = f(T_j)$


parameter: $I_D = 70 \text{ A}$, $V_{DD} = 25 \text{ V}$

$R_{GS} = 25 \Omega$



Drain-source breakdown voltage


$V_{(BR)DSS} = f(T_j)$



Typ. gate charge

$V_{GS} = f(Q_{Gate})$

parameter: $I_D \text{ puls} = 70 \text{ A}$



Edition 7.97

Published by Siemens AG,
Bereich Halbleiter Vertrieb,
Werbung, Balanstraße 73,
81541 München

© Siemens AG 1997

All Rights Reserved.

Attention please!

As far as patents or other rights of third parties are concerned, liability is only assumed for components, not for applications, processes and circuits implemented within components or assemblies.

The information describes a type of component and shall not be considered as warranted characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, delivery and prices please contact the Semiconductor Group Offices in Germany or the Siemens Companies and Representatives worldwide (see address list).

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Siemens Office, Semiconductor Group.

Siemens AG is an approved CECC manufacturer.

Packing

Please use the recycling operators known to you. We can also help you - get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Components used in life-support devices or systems must be expressly authorized for such purpose!

Critical components¹ of the Semiconductor Group of Siemens AG, may only be used in life-support devices or systems² with the express written approval of the Semiconductor Group of Siemens AG.

1)A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or effectiveness of that device or system.

2)Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or