


Leaded Metal Film Resistors with Established Reliability



MBA/SMA 0204 VG06, MBB/SMA 0207 VG06, and MBE/SMA 0414 VG06 leaded metal film resistors with established reliability are the perfect choice for all high-reliability applications typically found in military, aircraft and spacecraft electronics. These versions supplement the families of professional and precision leaded resistors MBA/SMA 0204, MBB/SMA 0207, and MBE/SMA 0414.

FEATURES

- IECQ-CECC approved to EN 140101-806, version E
- Established reliability, failure rate level E7
- Advanced thin film technology
- Fused pure tin (Sn) plating on copper (Cu) wire
- Single lot date code
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

APPLICATIONS

- Military
- Avionics
- Space

METRIC SIZE

DIN	0204	0207	0414
EN/CECC	A	B	D

TECHNICAL SPECIFICATIONS

DESCRIPTION	MBA/SMA 0204 VG06	MBB/SMA 0207 VG06	MBE/SMA 0414 VG06
EN/CECC Style (Size)	A	B	D
Resistance Range	1 Ω to 5.11 M Ω ; 0 Ω	1 Ω to 10 M Ω ; 0 Ω	1 Ω to 21.5 M Ω
Resistance Tolerance	$\pm 1\%$; $\pm 0.1\%$		
Temperature Coefficient	± 50 ppm/K; ± 15 ppm/K		
Operating Voltage, U_{max} , AC/DC	200 V	350 V ⁽¹⁾	500 V
Permissible Voltage Against Ambient (Insulation):			
1 Minute; U_{ins}	300 V	500 V	800 V ⁽¹⁾
Continuous	75 V	75 V	75 V
Assessed Failure Rate Level	E7 = 10^{-7} /h		
Quality Factor, π_Q	0.1		
Failure Rate, $FIT_{observed}$	$< 0.1 \times 10^{-9}$ /h		

Notes

- These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.
- The failure rate level E7 (10^{-7} /h, $\pi_Q = 0.1$), corresponding to MIL Level R, is superior to level E6 (10^{-6} /h, $\pi_Q = 0.3$) or level E5 (10^{-5} /h, $\pi_Q = 1$) and thus may be used as a replacement.

⁽¹⁾ These tightened requirements provide a user advantage over the requirements of EN140101-806.

TECHNICAL SPECIFICATIONS FOR PRODUCTS ± 50 ppm/K; $\pm 1\%$

DESCRIPTION	MBA/SMA 0204 VG06	MBB/SMA 0207 VG06	MBE/SMA 0414 VG06
Rated Dissipation P_{70}	0.4 W	0.6 W	1 W ⁽¹⁾
Permissible Film Temperature $\vartheta_{F max}$	155 $^{\circ}$ C		
Operating Temperature Range	- 55 $^{\circ}$ C to 155 $^{\circ}$ C		
Max. Resistance Change at P_{70} for Resistance Range, $ \Delta R/R $ max., after:	1 Ω to 332 k Ω	1 Ω to 1 M Ω	1 Ω to 2.43 M Ω
1000 h	$\leq 0.5\%$	$\leq 0.5\%$	$\leq 0.4\%$ ⁽¹⁾
8000 h	$\leq 1\%$	$\leq 1\%$	$\leq 0.8\%$ ⁽¹⁾



MBA/SMA 0204 VG06, MBB/SMA 0207 VG06, MBE/SMA 0414 VG06

Leaded Metal Film Resistors with Established Reliability Vishay Beyschlag

TECHNICAL SPECIFICATIONS FOR PRODUCTS ± 15 ppm/K; ± 0.1 %			
DESCRIPTION	MBA/SMA 0204 VG06	MBB/SMA 0207 VG06	MBE/SMA 0414 VG06
Rated Dissipation P_{70}	0.25 W ⁽¹⁾	0.4 W	0.65 W ⁽¹⁾
Permissible Film Temperature $\vartheta_{F \text{ max.}}$	125 °C		
Operating Temperature Range	- 55 °C to 125 °C		
Max. Resistance Change at P_{70} for Resistance Range, $ \Delta R/R $ max., after:	100 Ω to 221 k Ω	100 Ω to 499 k Ω	100 Ω to 470 k Ω
1000 h	≤ 0.25 %	≤ 0.15 % ⁽¹⁾	≤ 0.25 %
8000 h	≤ 0.5 %	≤ 0.5 %	≤ 0.5 %

Note

⁽¹⁾ These tightened requirements provide a user advantage over the requirements of EN140101-806.

PART NUMBER AND PRODUCT DESCRIPTION																	
PART NUMBER: MBB0207CE3523BCT00																	
PART NUMBER: MBB0207CZ0000ZCT00																	
M	B	B	0	2	0	7	C	E	3	5	2	3	B	C	T	0	0
M	B	B	0	2	0	7	C	Z	0	0	0	0	Z	C	T	0	0
TYPE and SIZE			VERSION			TCR			RESISTANCE				TOLERANCE		PACKAGING		
MBA/SMA 0204 MBB/SMA 0207 MBE/SMA 0414			C = EN 140101-806, version E, failure rate level E7			C = ± 50 ppm/K E = ± 15 ppm/K Z = Jumper			3 digit value 1 digit multiplier MULTIPLIER 8 = *10 ⁻² 9 = *10 ⁻¹ 0 = *10 ⁰ 1 = *10 ¹ 2 = *10 ² 3 = *10 ³ 4 = *10 ⁴ 5 = *10 ⁵ 0000 = Jumper				F = ± 1 % B = ± 0.1 % Z = Jumper		C1 CT		
PRODUCT DESCRIPTION: MBB/SMA 0207-15 0.1 % VG06 CT 352K																	
PRODUCT DESCRIPTION: MBB/SMA 0207 VG06 CT 0R0																	
MBB/SMA 0207		-15		0.1 %		VG06		CT		352K							
MBB/SMA 0207		-		-		VG06		CT		0R0							
TYPE and SIZE		TCR		TOLERANCE		VERSION		PACKAGING		RESISTANCE							
MBA/SMA 0204 MBB/SMA 0207 MBE/SMA 0414		± 50 ppm/K ± 15 ppm/K		± 1 % ± 0.1 %		VG06 = EN 140101-806, version E, failure rate level E7		C1 CT		49R9 = 49.9 Ω 352K = 352 kΩ 0R0 = Jumper							

Notes

- The products can be ordered using either the PART NUMBER or the PRODUCT DESCRIPTION.
- Products within a packaging unit are single lot date code.

EN 140101-806 ORDERING INFORMATION

Example of the ordering information for a resistor: MBB/SMA 0207-15 0.1 % VG06 352K
EN140101-806EZBP352KBE7

Example of the ordering information for a zero ohm jumper: MBB/SMA 0207 VG06 0R0
EN140101-806EZB-0R00-E7

The elements used in the component number have the following meaning:

EN140101-806	EN detail specification number
EZ	Assessment level for the zero-defect approach
B	Style (Size)
P	Temperature coefficient, according to EN60062
	R = ± 50 ppm/K; P = ± 15 ppm/K
352K	Resistance, according to EN60062, 4 characters
B	Tolerance on rated resistance, according to EN60062
	F = ± 1 %; B = ± 0.1 %
E7	Failure rate level according to EN60115-1, Annex ZR

Notes

- The ordering information according to EN 140101-806:2007 shown above succeeds and replaces the ordering information according to its predecessor CECC 40101-806, for example:
CECC 40101-806 S B E 352K B E7
with S Assessment level, where EZ is successor to and superior replacement for S
E Temperature coefficient, according to the detail specification
C = ± 50 ppm/K; E = ± 15 ppm/K
- EN 140101-806 succeeds the prior specification CECC 40101-806 and a huge variety of historical specifications CECC 40101-0xx. Preceding specifications on resistors with established reliability (now "Version E") have been CECC 40101-046 and CECC 40101-047.

TEMPERATURE COEFFICIENT AND RESISTANCE RANGE

DESCRIPTION		RESISTANCE RANGE		
TCR	TOLERANCE	MBA/SMA 0204 VG06	MBB/SMA 0207 VG06	MBE/SMA 0414 VG06
± 50 ppm/K	± 1 %	1 Ω to 5.11 M Ω	1 Ω to 10 M Ω	1 Ω to 21.5 M Ω
± 15 ppm/K	± 0.1 %	100 Ω to 221 k Ω	100 Ω to 499 k Ω	100 Ω to 470 k Ω
Jumper		≤ 10 m Ω ; $I_{\max.} = 3$ A	≤ 10 m Ω ; $I_{\max.} = 5$ A	-

Note

- According to EN140101-806, resistance values are to be selected from the E96 series for ± 1 % tolerance and from the E192 series for ± 0.1 % tolerance.

PACKAGING

TYPE	CODE	QUANTITY	PACKAGING STYLE	WIDTH	PITCH	PACKAGING DIMENSIONS
MBA/SMA 0204 VG06	C1	1000	Taped acc. IEC 60286-1, fan-folded in a box	53 mm	5 mm	184 mm x 75 mm x 42 mm
	CT	5000				330 mm x 75 mm x 55 mm
MBB/SMA 0207 VG06	C1	1000		53 mm		184 mm x 75 mm x 42 mm
	CT	5000				324 mm x 77 mm x 83 mm
MBE/SMA 0414 VG06	C1	1000		63 mm		377 mm x 85 mm x 47 mm

Notes


- Width is the nominal spacing between tapes, with the nominal tape width on both sides being 6 mm, and pitch is the nominal standard spacing between components; tolerances apply according to IEC 60286-1.
- The tape on one side is marked with a black print every 100th component position.



MBA/SMA 0204 VG06, MBB/SMA 0207 VG06, MBE/SMA 0414 VG06

Leaded Metal Film Resistors with Established Reliability Vishay Beyschlag

DIMENSIONS



DIMENSIONS AND MASS

TYPE	D _{max.} (mm)	L _{max.} (mm)	I _{min.} (mm)	d _{nom.} (mm)	M _{min.} (mm)	MASS (mg)
MBA/SMA 0204 VG06	1.6	3.6	29	0.5	5	125
MBB/SMA 0207 VG06	2.5	6.3	28	0.6	10	220
MBE/SMA 0414 VG06	4.0	11.9	31	0.8	15	700

Note

- Color code marking is applied according to IEC 60062 ⁽³⁾ in five bands. Each color band appears as a single solid line, voids are permissible if at least $\frac{2}{3}$ of the band is visible from each radial angle of view. The last color band for tolerance is approximately 50 % wider than the other bands. Zero ohm jumpers are marked with one centered black color band. An interrupted violet band between the 1st and 2nd full band indicates the failure rate level E7. An interrupted orange band between the 4th and 5th full band indicates the temperature coefficient of 15 ppm/K.

DESCRIPTION

Production is strictly controlled and follows an extensive set of instructions established for reproducibility. A homogeneous film of metal alloy is deposited on a high grade ceramic body (Al_2O_3) and conditioned to achieve the desired temperature coefficient. Plated steel termination caps are firmly pressed on the metallised rods. A special laser is used to achieve the target value by smoothly cutting a helical groove in the resistive layer without damaging the ceramics. Connecting wires of electrolytic copper plated with 100 % pure tin are welded to the termination caps. The resistor elements are covered by a light blue protective coating designed for electrical, mechanical and climatic protection. Five colour code rings designate the resistance value and tolerance in accordance with IEC 60062 ⁽³⁾.

The result of the determined production is verified by an extensive testing procedure performed on 100 % of the individual resistors. For IECQ-CECC approved products, this includes pulse load screening for the elimination of products with a potential risk of early life failures according to EN 140101-806, 2.1.2.2 (feasible for $R \geq 10 \Omega$). Only accepted products are stuck directly on the adhesive tapes in accordance with IEC 60286-1 ⁽³⁾. Products within a package unit are from the same production lot and carry the same date code.

ASSEMBLY

The resistors are suitable for processing on lead forming and cropping equipment and automatic insertion machines. They are suitable for automatic wave or reflow soldering, including miniature wave selective soldering. Solderability is specified for 2 years after production or requalification, however, the permitted storage time is 20 years.

The resistors are completely lead (Pb)-free, the fused pure tin plating provides compatibility with lead (Pb)-free soldering processes. The immunity of the plating against tin whisker growth has been proven under extensive testing.

The encapsulation is resistant to all cleaning solvents commonly used in the electronics industry, including alcohols, esters and aqueous solutions. The suitability of conformal coatings, if applied, shall be qualified by appropriate means to ensure the long-term stability of the whole system.

All products comply with the GADSL ⁽¹⁾ and the CEFIC-EECA-EICTA ⁽²⁾ list of legal restrictions on hazardous substances. This includes full compliance with the following directives:

- 2000/53/EC End of Vehicle Life Directive (ELV) and Annex II (ELVII)
- 2011/65/EU Restriction of the use of Hazardous Substances Directive (RoHS)
- 2002/96/EC Waste Electrical and Electrical Equipment Directive (WEEE)



APPROVALS

The resistors are approved within the IECQ-CECC Quality Assessment System for Electronic Components to the detail specification **EN140101-806** which refers to **EN60115-1**, **EN140100** and the variety of environmental test procedures of the **IEC 60068** ⁽³⁾ series.

Conformity is attested by the use of the **CECC** logo (E) as the Mark of Conformity on the package label.

Vishay BEYSCHLAG has achieved “**Approval of Manufacturer**” in accordance with **IEC QC 001002-3, clause 2**. The release certificate for “**Technology Approval Schedule**” in accordance with **CECC 240001** based on **IEC QC 001002-3, clause 6** is granted for the Vishay Beyschlag manufacturing process.

The Vishay BEYSCHLAG production facility is registered with the CAGE code D9539.

Notes

⁽¹⁾ Global Automotive Declarable Substance List, see www.gadsl.org.

⁽²⁾ CEFIC (European Chemical Industry Council), EECA (European Electronic Component Manufacturers Association), EICTA (European trade organisation representing the information and communications technology and consumer electronics), see www.eicta.org/index.php?id=1053&id_article=340.


⁽³⁾ The quoted IEC standards are also released as EN standards with the same number and identical contents.

RELATED PRODUCTS

A wider range of TCR, tolerance and resistance values, plus the option of values from a different E series is available with products approved to **EN140101-806**, version A, without established reliability, nominal failure rate level E0 (Quality factor $\pi_Q = 3$). See the datasheets:

- “Professional Leaded Metal Film Resistors”
(www.vishay.com/doc?28766)
- “Precision Leaded Metal Film Resistors”
(www.vishay.com/doc?28767)

FUNCTIONAL PERFORMANCE




Derating for Products ± 50 ppm/K; ± 1 %




MBA/SMA 0204 VG06, MBB/SMA 0207 VG06, MBE/SMA 0414 VG06

Leaded Metal Film Resistors with Established Reliability Vishay Beyschlag



Derating for Products ± 15 ppm/K; ± 0.1 %




In accordance with IEC 60195

Current Noise - A_1 ⁽¹⁾

Note

⁽¹⁾ These tightened requirements provide a user advantage over the requirements of EN140101-806.



In accordance with IEC/TR 60440

Non-Linearity - A_3



FUNCTIONAL PERFORMANCE

Further information on the performance of these products is given in the following datasheet:

- "Professional Leded Metal Film Resistors"
(www.vishay.com/doc?28766)
- "Precision Leded Metal Film Resistors"
(www.vishay.com/doc?28767)

HISTORICAL 12NC INFORMATION

- The resistors had a 12-digit numeric code starting with 2312
- The subsequent 4 digits indicated the resistor type, specification and packaging; see the 12NC table
- The remaining 4 digits indicated the resistance value:
 - The first 3 digits indicate the resistance value
 - The last digit indicated the resistance decade in accordance with the resistance decade table

TEST AND REQUIREMENTS

All tests are carried out in accordance with the following specifications:

- EN60115-1, generic specification
- EN140100, sectional specification
- EN140101-806, detail specification

For further information on the tests and requirements of these products please refer to the specifications mentioned above, and to the following datasheet:

- "Professional Leded Metal Film Resistors"
(www.vishay.com/doc?28766)
- "Precision Leded Metal Film Resistors"
(www.vishay.com/doc?28767)

RESISTANCE DECADE

RESISTANCE DECADE	LAST DIGIT
1 Ω to 9.99 Ω	8
10 Ω to 99.9 Ω	9
100 Ω to 999 Ω	1
1 k Ω to 9.99 k Ω	2
10 k Ω to 99.9 k Ω	3
100 k Ω to 999 k Ω	4
1 M Ω to 9.99 M Ω	5
10 M Ω to 99.9 M Ω	6

Historical 12NC Example

The 12NC of a MBB 0207 VG06 resistor, resistance 352K, TCR 15, ± 0.1 % tolerance, supplied taped and fan-folded in a box of 5000 units was: 2312 917 03524.

HISTORICAL 12NC - Resistor type and packaging

DESCRIPTION			2312	
			TAPED, FAN-FOLDED IN A BOX	
TYPE	TCR	TOL.	C1 1000 PIECES	CT 5000 PIECES
MBA 0204 VG06	± 50 ppm/K	± 1 %	900 0...	905 0...
	± 15 ppm/K	± 0.1 %	902 0...	907 0...
	Jumper		902 90001	907 90001
MBB 0207 VG06	± 50 ppm/K	± 1 %	910 0...	915 0...
	± 15 ppm/K	± 0.1 %	912 0...	917 0...
	Jumper		912 90001	917 90001
MBE 0414 VG06	± 50 ppm/K	± 1 %	920 0...	-
	± 15 ppm/K	± 0.1 %	922 0...	

Note

- The 12NC coding had been established for the series of MBA 0204 VG06, MBB 0207 VG06 and MBE 0414 VG06 products. These products are succeeded and replaced by the new series of MBA/SMA 0204 VG06, MBB/SMA 0207 VG06 and MBE/SMA 0414 VG06 products, for which the 12NC coding is no longer applicable.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.